



The diagram illustrates the components of the power adapter kit, organized into four sections labeled A through D:

- A:** A black power adapter unit with a 5-pin DIN connector on the left and a USB Type-A port on the right.
- B:** A black USB Type-A to USB Type-B cable.
- C:** Power plug adapters for different regions:
 - EU Only:** A Type C plug with two round pins.
 - GB Only:** A Type G plug with three rectangular pins.
 - EU / GB:** A Type C plug with a removable Type G plug attached to its side.
- D:** A white user manual with the text "user manual" printed on it.

Notebook **PC**

GB Data Connection
FR Connexion de données
D Datenanschluss
PT Conexão de dados
ES Conexión de datos
JP データの接続
CN 数据连接

GB Power Connection
FR Connexion d'alimentation
D Stromanschluss
PT Conexão de energia
ES Conexión de la alimentación
JP 電源の接続
CN 电源连接

akasa

USB-A **USB-C**

LED

GB high performance USB fast charging controller provide auto detect and charging
FR contrôleur de charge rapide USB de haute performance fournissant la détection automatique et la charge
D Leistungsstarker USB Schnelllade-Controller mit automatischer Erkennung und Ladung
PT USB de alta performance com sistema de reconhecimento automático e recarga rápida
ES controlador de carga rápida USB de alto rendimiento con detección y carga automática
JP 高性能USB高速充電コントローラは自動検出および充電機能に対応
CN 高性能USB快速充电控制器提供自动检测和充电

The diagram illustrates the front and top views of the akasa A6000S power supply unit. The top view shows the input terminals labeled 'c' (DC 5V) and 'd' (GND). The front view shows the output ports labeled 'a' (USB ports) and 'b' (charging ports).

2014/2/V